			CANUTA	DV DDECCI	IDE TO AN	CNAITTED	A DT4.0		SHEET: 1 of 2
	SANITARY PRESSURE TRANSMITTER - APT10 REVISION BY CHECK APPROVED DATE DATE Control of the c					ALTUS N			
all		4	REVISION	ВҮ	CHECK	APPROVED	DATE	CUSTOM	IER
00								CUSTOM	IER N°:
DESCRIPTION			•	TAG NUMBER:		PIT-XXXX	N	ODEL:	APT10 - HS-XXXXXXXXX-XX-XXXX
OUTPUT /	PROTOCOL	Н	4 - 20 mA / Ha	art 7	•		•		OBSERVATION
SENSOR	TYPE	S	SANITARY						
	RANGE -	2	-37,4 a 37,4 kPa (-3814 a 3814 mm H20)						
		3	-147,1 a 147,1 kPa (-1,5 a 1,5 kgf/cm²)					THE RANG	GE CAN BE EXTENDED UP TO 0.8LRL AND 1.2URL WITH
		4	-690 a 690 kPa (-7 a 7 kgf/cm²)						SMALL DEGRADATION OF ACCURACY.
		5	-2068 a 2068 kPa (-21 a 21 kgf/cm²)						
DIADUDACAAAATEDIAI		I	STAINLESS STEEL 316L						
DIAPHRAGM MATERIAL FILLING FLUID		Н	HASTELLOY C276						
		S	SILICONE OIL						
FILLING	O FLUID	F	FLUOROLUBE						
	APTER/PURGE ERIAL	I	STAINLESS ST	EEL 316					
		0	WITHOUT PURGE						
DUDGE			OPPOSITE SID	E TO PROCESS	CONNECTION				
PURGE POSITION -		2	UPPER						
		3	LOW						
		В	BUNA-N						
CELL SEA	LING RING	٧	VITON						
		T	TEFLON						
PROCESS (CONECTION	0	1/4" - 18NPT (WITHOUT ADAPTER)						
(REFERENCE OUTLET)		1	1/2" - 14NPT (WITH ADAPTER)						
			TRICLAMP 1 1/2" WITHOUT EXTENSION						
	-	2	TRICLAMP 2" 150 WITHOUT EXTENSION						
PROCESS CONECTION (SANITARY		3	TRICLAMP 2" 150 WITH EXTENSION						
	PROCESS CONECTION (SANITARY OUTLET)		SMS 1 1/2" WITHOUT EXTENSION						
			SMS 2" 150 WITHOUT EXTENSION						
	-	6	SMS 2" 150 W	ITH EXTENSIO	N				
	CTION MATERIAL Y OUTLET)	I	STAINLESS STEEL 316						
FILLING FLUID I	N THE SANITARY	S	SILICONE DC200						
OU	TLET	N	GLYPOL PROP	YLENE (NEOBE	E)				
SANITARY OUTLET DIAPHRAGM MATERIAL		I	STAINLESS STEEL 316						
		Н	HASTELLOY C276						
SANITARY OUT			WITHOUT SEA	LING RING					
	OUTLET SEALING MATERIAL	В	BUNA-N						
		٧	VITON						
KING IVI		Т	TEFLON						
		0	WITHOUT GLOVE						
ADAPTAT	ION GLOVE	1	STAINLESS STEEL 316L GLOVE						
NOTES:	Į.								

								SHEET:	2	of :
-14		SANITA	RY PRESSU	JRE TRAN	SMITTER -	VPT10	ALTUS N°:	OHEE!	0	
altus		REVISION	BY	CHECK	APPROVED	DATE	CUSTOMER		0	
	,						OLIGICA AFD NO			
							CUSTOMER N°:		0	
	0	WITHOUT CER	TIFICATE			[]			
TYPE OF CERTIFICATION	1	INTRINSIC SECURITY]			
	2	EXPLOSION-PROOF]			
	0	WITHOUT CERTIFICATE				1				
CERTIFYING ENTITY	1	INMETRO]			
	А	ALUMINUM]				
HOUSING MATERIAL	ı	STAINLESS STEEL]				
ELECTRICAL CONNECTION	1	1/2" - 14NPT								
	0	NO PAINTING C]				
PAINTING	1	BLUE - RAL 5005]			
	2	BLUE - PETROBRAS]			
IDENTIFICATION PLATE	P0	WITH IDENTIF	ICATION PLAT	E		Е]			
CALIBRATION CERTIFICATE	CO	TRACEABLE RE	3C]			